

## FIRE HOODS & DOWNLIGHT COVERS

FIREFLY™ Fire Hoods and Downlight Covers are designed to provide fire protection over the recessed luminaire or downlight in a fire rated ceiling.

In the event of a fire the Fire Hood or Downlight Covers will delay the progress of fire and smoke travelling through a ceiling, thereby providing precious time for occupants to safely exit the building and emergency services to minimise fire damage.

FIREFLY™ fire barriers are made by TBA Protective Technologies Ltd: protecting people and property around the world.

DESCRIPTION	Lightweight fire protective cover suitable for recessed luminaires or downlights of various sizes
CERTIFICATION	Third Party Certified by IFCC. Certificate number: IFCC 1564
APPLICATION	Can be installed from above or below
SPECIFICATION	BS476 Part 23:1987, clause 5 – 60 minutes
	Assessed for use with plasterboard – 60 minutes
	Suitable for use under timber floors, assembly with plasterboard & suspended ceiling system – 60 minutes
	Suitable for use under timber floor
	Assembly protected with fire-rated suspended ceiling system – 30 minutes
CLASSIFICATION	BS 476 Class "0" BUILDING REGULATIONS – Complies with requirements
	BS 476 Part 6 Fire Propagation test – Fire propagation index 2.56
	BS 476 Part 7 surface spread of flame – Certification to "class1" pass

## Advanced Materials for Demanding Environments

04/20-1

