

## DECLARATION OF PERFORMANCE

According to Annex III of Regulation (EU) Nr. 305/2011 (Construction Products Regulation)

### QUELFIRE QSS – ACRYLIC SEALANT

1. **Unique identification code of the product-type:**  
Quelfire QSS Acrylic Sealant
2. **Type, batch or serial number as required pursuant to Article 11(4):**  
See batch number displayed on the product
3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification:**  
Fire stopping and sealing product for penetration seals, see ETA 17/0788

Cable penetrations	Insulated & non insulated, cables, cable trays & cable ladders	<b>The field of application has to comply with the content of the related ETA 17/0788</b>
Pipe penetrations	Insulated & non insulated metal pipes	<b>The field of application has to comply with the content of the related ETA 17/0788</b>

4. **Name, registered trade name or registered trade mark and contact address as required pursuant to Article 11(5):** Quelfire Ltd, Unit 3, Millbuck Way, Springvale Industrial Estate, Sandbach, Cheshire, CW11 3HT, Tel: 0161 928 7308, Email: [sales@quelfire.co.uk](mailto:sales@quelfire.co.uk)
5. **Authorised representative:** n.a.
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:** System 1
7. **Harmonised standard:** n.a.
8. **In the case of the declaration of performance concerning product covered by a Harmonised Standard and/or ETA:** Warrington Certification Ltd issued ETA Number 17/0788 on the basis of Guideline for European Technical Approval of Fire Stopping and Fire Sealing Products: ETAG 026 Part 1: "General" and Part 2: "Penetration Seals" performed initial and continuous surveillance of the place of manufacture and the factory production control implemented, sampled product and witnessed initial type testing under system 1 and issued the Certificate of Constancy of Performance 1121-CPR-JA5116
9. **Declared performance:**

Essential Characteristic	Declared performance/Harmonised technical specification
<b>Reaction to fire</b>	Class F according to EN 13501-1
<b>Resistance to fire</b>	Resistance to fire performance and field application in accordance with EN 13501-2 see ETA 17/0788
<b>Air Permeability</b>	Tested in accordance with EN 1026, see ETA 17/0788
<b>Dangerous substances</b>	See ETA 17/0788 – Declaration – compliant
<b>Airbourne Sound Insulation</b>	Tested in accordance with EN ISO 10140-2:2010 & EN ISO 140-3 & EN ISO 717-1, see ETA 17/0788
<b>Durability and serviceability</b>	Z <sup>1</sup> (0/+40°C) intended for use at internal conditions with high humidity (85%) in accordance with EOTA Technical Report – TR024
<b>Movement Capability</b>	According to ISO 11600 : ISO 11600 – F – 12.5p.
<b>Other</b>	Not applicable/No performance determined

10. **The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer.



Keith Wells  
Managing Director  
Quelfire Ltd



Darryl Wells  
Product Development  
Quelfire Ltd